

DIAMOND DRILLING RIGS



TS402HD, TS402, TS252 Rigs

TS402HD, TS402, TS252 DRILLING RIGS

We have a comprehensive range of diamond drilling rigs to cover most applications.

The rigs can be fixed by means of a rawlbolt anchor for either horizontally or vertically drilling.

Angled holes can also be achieved.

The rigs are ergonomic, user friendly and also come apart for easy handling.

Advantages:

- Diamond drills can drill various sized holes in various stone materials including reinforced concrete
- On exiting the hole there is no spooling - therefore no making good is required
- Whilst drilling, the tips of the drill are cooled with water -therefore keeping dust problems to a minimum
- By means of drilling holes side by side (known as stitch drilling), large areas of masonry or concrete can be removed
- By means of extension rods, holes can be drilled to greater depths
- Diamond drilling is also non percussive and therefore there is no vibration.

Post & Arm Angular Rig



TECHNICAL DATA

TS 402HD RIG AND R2531 MOTOR

- Motor Drilling Range 400mm Diameter
- Height 1.100 Metres
- Power 110 Volt

TS 402 RIG AND R2221 MOTOR

- Motor Drilling Range 200mm Diameter
- Height 1.000 Metres
- Power 110 Volt

TS 252 RIG AND R1721 MOTOR

- Motor Drilling Range 150mm Diameter
- Height 803mm
- Power 110 Volt

DRILLING ACCESSORIES

Transformers 110 volt leads, fixing kits, water pumps, percussion drills and diamond cores available on request.

